

PIPES FOR CABLE CONDUITS UNI 7683

Seamless and welded galvanized and threaded pipes

USE Flameproof, explosion-proof electrical systems (AD-PE)

STEEL GRADE Fe360

PROCESSING

- ▶ Seamless
- ▶ Welded (F.M.-L.C.-ERW)

TOLERANCES **THICKNESS**

- + not specified (delimited by mass) / -12,5%

OUTSIDE DIAMETER

NPS	Diameter (mm)		Thickness (mm)	Pipemass (kg/m)
	Max	Min		Threaded coupled and galvanized
1/2	21,7	21,0	2,3	1,19
3/4	27,1	26,4	2,3	1,50
1	34,0	33,2	2,9	2,33
1 ¼	42,7	41,9	2,9	2,99
1 ½	48,6	47,8	2,9	3,45
2	60,7	59,6	3,2	4,83
2 ½	76,3	75,2	3,2	6,15
3	89,4	87,9	3,6	8,15
4	114,9	113,0	4,0	11,70

MASS

- +/- 10% on individual pipe
- +/- 7,5% on batch of 10 tons min

MARKING Manufacturer's name and/or trademark AD UNI 7683

CERTIFICATION On request a conformity declaration according to UNI EN 10204 can be issued; a certificate of control or inspection, or an inspection report may also be requested during the order